



FC PATCH-CORD

APPLICATIONS

- CATV
- Metro
- Test equipment
- Active device termination
- Local Area Networks (LANs)
- Premise installations
- Telecommunication networks
- Data processing networks
- Wide Area Networks (WANs)

FEATURES

- Low insertion loss and back reflection loss
- Good Durability
- Standard: Telcordia GR-326-CORE
- Good exchangeability
- High temperature stability

AVAILABILITY

- Simplex/Duplex patch-cord available
- Pigtail available
- Fan-out available
- Various boot (cable) sizes available

SPECIFICATIONS

	Single mode	Multimode
Insertion Loss	≤0.25dB	≤0.25dB
Return Loss	≥50 dB (PC) ≥65 dB (APC)	
Repeatability	≤0.1	
Durability	≤0.2 dB typical change, 1000 matings	
Interchangeability	≤0.2dB	
Tensile strength	>10kg	
Operating Temperature	-40 to + 85°C	-40 to + 85°C

ORDERING OPTIONS

Boot (cable) Size	Boot Color	Fiber Type	Cable number	Application	Length
0.9mm	Black	9/125µm (SM)	Simplex	PC	Customized
2.0mm	Green	50/125µm (MM)	Duplex	APC	
3.0mm	Red	62.5/125µm (MM)	Fan-out (4f)		
			Fan-out (6f)		
			Fan-out (8f)		
			Fan-out (12f)		



www.koceleurope.com