

## MSAT

### Mid-Span Access Tool



- Quickly and easily access fibers in 2, 2.5 and 3mm buffer tubes in a mid-span location without fiber damage
- All blades precisely factory mounted in tube slitting channels with no adjustment required by the installer
- Tool design incorporates buffer tube size gages on the tool body for ease of selecting proper tube slitting channel
- Convenient spring loaded lever opens and closes the tool and lever becomes flush with the top of the tool body when closed
- For use with the following diameter buffer tubes:
  - 2.0mm 1.8-2.2 mm (0.071" - 0.086")
  - 2.5mm 2.3-2.8 mm (0.090" - 0.110")
  - 3.0mm 2.8-3.2 mm (0.110" - 0.126")
- Made in the U.S.A
- Replacement Blade: Part No: 80794 includes 1 blade set (2 each) and 1/16" Allen wrench
- Same Blade Part Number for all three tool channels
- Length: 2.5in (63.5mm)
- Weight: 8oz (226.7g)
- Part No.: 80785

## 405

### Fiber Buffer Tube and Drop Cable Slitter



- For mid-span and end slitting of fiber buffer tubes and fiber drop cable
- Different models available matched to the size of buffer tube or drop cable to be prepared
- Dual blade design
- Self closing for safety
- Latch locks tool closed
- Comfortable soft plastic grips
- Made in the U.S.A.
- Replacement Blade Part No.: 80235 (2 required)
- Length: 6.5 in (165 mm)
- Weight: 9.0 oz (255 g)

Model	Part NO.	Tube Size (mm OD)	Tube Size (inch OD)
405 - 1.8 mm	80800	1.6 - 1.8 mm	0.063" - 0.071"
405 - 2.0 mm	80805	1.8 - 2.0 mm	0.071" - 0.079"
405 - 2.2 mm	80801	2.0 - 2.2 mm	0.079" - 0.087"
405 - 2.5 mm	80802	2.3 - 2.5 mm	0.091" - 0.098"
405 - 3.0 mm	80803	2.7 - 3.0 mm	0.106" - 0.118"
405 - 3.3 mm	80804	3.0 - 3.3 mm	0.118" - 0.130"
*405 - Drop A	80256	4.4 x 8.2 mm	0.175" - 0.325"

\* 405 - Drop A for OFS, CommScope, Corning, Draka/Conteg, OFS, Prysmian and Sumitono cable

FIBER OPTICS

ELECTRICAL

ELECTRONICS

TELECOM