



ST PATCH-CORD

APPLICATIONS

- Local Area Networks (LANs)
- Instrument

- Data processing networks
- Premise installations

FEATURES

- Low insertion loss and back reflection loss
- Good Durability
- Standard: Telcordia GR-326-CORE

- Good exchangeability
- High temperature stability

AVAILABILITY

- Simplex/Duplex patch-cord available
- Pigtail available

- Fan-out available
- Various boot (cable) sizes available

SPECIFICATIONS

	Single mode	Multimode
Insertion Loss	≤0.20dB	≤0.25dB
Return Loss	≥50 dB	
Repeatability	≤0.1	
Durability	≤0.2 dB typical change, 1000 matings	
Interchangeability	≤0.2dB	
Tensile strength	>10kg	
Operating Temperature	-40 to + 85°C	-40 to + 85°C

ORDERING OPTIONS

Boot (cable) Size	Boot Color	Fiber Type	Cable number	Length
0.9mm	Black	9/125µm (SM)	Simplex	Customized
2.0mm	Red	50/125µm (MM)	Duplex	
3.0mm	Brown	62.5/125µm (MM)	Fan-out (4f)	
			Fan-out (6f)	
			Fan-out (8f)	
			Fan-out (12f)	



www.koceleurope.com