


Osprey® 700e HD

Video Capture Card



Designed for Live in HD with SD Switching On-the-Fly

ViewCast's first high-definition (HD) card for the Osprey® family, the Osprey 700e HD comes with standard-definition (SD) switching on-the-fly, legendary Osprey performance, and the latest PCI Express™ technology.

Already making a splash, the Osprey 700e HD won Streaming Media's 2008 Readers Choice Award and TV Technology magazine's 2007 STAR Award and was featured in HD Video Pro magazine's February 2008 issue.

Designed for Live Exclusive Adaptive Features.

The Osprey 700e HD card comes with Designed for Live™ features which distinguishes it from many cards used for ingesting video into video editing systems or other applications.

Multiple Streams Per Input.

Purchase the Osprey 700e HD with SimulStream and you can:

- Feed multiple encoders at the same time.
- Use with a variety of available streaming codecs to easily create and manage live streams.
- Supports SD and HD streams.
- Create multiple streams of the same type with completely independent settings for sizing, scaling, logos, and bit rates.

Industry-proven performance.

Over 300,000 Osprey cards are out in the marketplace worldwide being used in a wide variety of broadcast, commercial and industrial applications. You'll find Osprey capture cards in mission-critical applications throughout the world.

Ideal Solution for:

- > Broadcasters
- > Government
- > Global OEM System Integrators

Applications


- > Webcasting
- > Live streaming
- > Podcasting
- > Mobile TV
- > Video-on-demand

Key Attributes

- > Accepts both Standard Definition and High-Definition inputs
- > Automatically adapts between SD and HD signals via Designed for Live features
- > On-the-Fly HD to SD downscaling
- > High-powered PCI Express bus for maximum performance
- > SimulStream option enables:
 - Completely independent settings for sizing, scaling, and bit rate speeds, plus logo overlays with dynamic positioning
 - A multitude of simultaneous video format outputs, including MPEG-4, RealNetworks, Windows Media and Adobe Flash
 - Instant Video-On-Demand (VOD), allowing your live stream to become instantly available as VOD content
- > Low-profile architecture for form-factor constrained environments
- > Professional broadcaster features, such as Loss of Video Detection, color space conversion, automatic telecine detection and processing, and automatic optimization for changing motion content

Osprey® 700e HD

Video Capture Card



Section/Chart Heading

Name	Rates	Resolution	Aspect Ratio
480i	30 / 29.97	720 x 480	4:3
576i	25	720 x 576	4:3
576p	50 / 25	720 x 576	4:3
720p	60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98	1280 x 720	16:9
1080i	60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98	1920 x 1080	16:9
1080p	30 / 29.97 / 25 / 24 / 23.98	1920 x 1080	16:9

Encoding Formats

- DirectShow® compatible

Inputs:

Video:

- SDI (BNCx1)

Audio:

- Embedded SDI (16 channel)

Outputs:

Video:

- SDI Pass through

Audio:

- Embedded SDI

Connectivity:

PCI Express (X1):

- Slots: X1, X4, X8, or X16

Processing:

Pre-processing:

- Scaling, cropping, de-interlacing, inverse telecine, closed caption rendering

Dimensions:

- Full Height, Half Length Board
- 6.60" L x 2.71" H (16.77cm L x 6.89cm H)

Hardware Warranty:

- 2 Year limited hardware warranty

